



טל 03-9190194
פקס 076-5104122
מייל taillift.info@gmail.com

DL 500/750/950



- ✓ For transporter chassis to 6.5 t permissible total weight
- ✓ Super net weight from 225 kg
- ✓ Durable 4 cylinder technology
- ✓ Reliable and fail-safe

The **DAUTEL LIFTER** brings cutting edge developments together with components proven 1000-fold to make for an unbeatable cost-benefit relationship.



And this makes the transportation of heavy loads for you especially easy:

- DL 500/750 rated load 500/750 kg at a load centre of 600 mm, DL 950 rated load 1000 kg at a load centre of 500 mm from the end of the superstructure/centre of the platform.
- 2 lift and tilt cylinders with piston rod protection each. The platform opens hydraulically.
- Double malfunction back-up provided by two separate, externally-controlled, control circuits and the traversable, when under load, 2-point foot control.
- Quiet, service-friendly 12 volt 0.8 kW or 24 volt 1.2 kW drive with thermal overload switch.
- Automatic tilting on the ground.
- Permanently maintenance-free compound bearing bushings Limited maintenance, reliable customer service.

The result is a tail-gate lift of the highest quality, designed for unbeatable safety, built for dependability during continuous use by our professional customers.



Type A slim design

Hot-dip galvanised hoist gear with slim lifting arm for installation "between" the transporter chassis frame of up to 5 t, primarily for Iveco Daily, Mercedes-Benz Sprinter/ VW-Crafter. Generous amount of free space for standard lighting = superstructure outer width -hoist gear outer width of 750 mm. Max. platform width 2300 mm. Super net weight from 225 kg

Type B wide design

KTL-painted hoist gear RAL 9005, optionally hot-dip galvanised with wide, warp-resistant lifting arm for installation on the "outside" of transporter chassis frames, primarily for Iveco Daily up to 6.5 t, Mercedes-Benz Sprinter/VW-Crafter up to 5 t, trailers up to 3.5 t and mini semitrailers up to 10 t, others on request. Free space for standard lighting = superstructure outer width -hoist gear outer width of 1480 mm. Max. platform width 2520 mm. Net weight from 245 kg

Durable platforms

Type C with longitudinal fluting, ideal for an advertising text, bolted KTL-painted connecting head. Height 1450/1600 mm, for DL 500/750B 1800 mm. Optional type V1 drop-down protector, 720 mm wide, for 1 or 2 roller containers with wheel Ø of max. 120 mm depending on platform width

Fast and easy installation

Especially fast and easy due to screw assembly. Max. loading height 1160 mm. 3-part rigid under-run guard, optionally available with tow bar for ball-type coupling, D-value 20.5 kN.



Edition 09/2010 · Technical data subject to change, illustrations non-binding.

טל 03-9190194
פקס 076-5104122
מייל taillift.info@gmail.com

